



VX 86



Packaging data

Sales unit	1 pcs.
Packaging volume shipping package	1.2 dm ³
Gross Weight shipping unit	0.871 kg
EAN	4010056163457
Article number	16345
Customs tariff number	85437030

Technical data

Downstream	
Inputs	1 pcs.
Frequency range DS	47...862 MHz
Gain DS	18...21 dB
Noise figure DS	<8 dB
Loss DS	0...18 dB
Equalizer DS	3...18 dB
Interstage equalizer DS	3 dB (constant)
Output level 1	96 dB μ V (DS, CENELEC 42 channels, flat)
Output level 2	98.5 dB μ V (DS, CENELEC 42 channels, 6 dB slope)
Output level 3	114 dB μ V (DS, EN50083-5, 3.Ord.)
Return path	
Frequency range US	5...30 MHz (passive)
Connectors	
F-socket	2 pcs.
General data	
Operating voltage AC	230 V (50/60 Hz)
Power consumption	3.5 W
Screening factor	dB Class A, EN 50083-2
Dimensions (width x height x depth)	163x90x47 mm
Operating temperature range	-20...+55 °C
Protection class	IP20
Lightning protection	1 kV (EN61000-4-5, 1,2/50 μ s pulse)

Title

VX 86

Short description

In-house amplifier

Description

In-house amplifier

Long text

With passive return path

Adjustable level and equalizer

F-connectors

Wall mounting

Metal housing